



MOBILE COMPUTER
HF550X

Smartphone-style mobile computer that can increase work productivity with barcode scanner

- 01 True smartphone-style with ergonomics design**
- 02 Enterprise level mobile computer**
- 03 More wireless connections**
- 04 Support fingerprint functionality to enhance job security and support worker authentication**
- 05 Business Optimization Solution BOS™ Software**
- 06 Sufficient battery capacity for use without charging stress**

Industry and applications

- Distribution (Retail)
 - Customer Engagement
 - BOPIS (Online Purchase, Store Receipt)
 - Store Shelf Management
 - Backroom Management
- Logistics warehouse
 - Wear it
 - Stock replenishment
 - Shipping/Trucking
- Customer service
 - Order
- Healthcare
 - EMR/EHR
 - Pharmacy Management

BOS™ Solution

- BOS™ Provisioning
- BOS™ Staging
- BOS™ Kiosk
- BOS™ Virtual Key
- BOS™ Enterprise Keyboard
- BOS™ VoIP, PTT, PTT Express
- BOS™ EMM
- BOS™ Wi-Fine™ (WiFi analyze application)
- BOS™ SecureID

3rd Party Solutions Integration

- EMM : Airwatch, MobileIron, Mobicontrol, IBM Mass360, VMWare
- PTT : ESChat, Zello, IMPTT, EveryTalk, AirPTT

Bluebird maintenance service(up to 8 years)

- BluebirdCare™
- BluebirdCare™ TCS
- Bluebird SecureCare™

STRONG POINTS



OS
Android 10
(Upgradeable to Android 14)



Performance
Octa-Core Processor



Wireless
Wifi,Bluetooth Support



Battery
User replaceable battery
3.8V / 4000 mAh



Drop Resistance
Multiple 1.2 m (4 ft) drop per
MIL-STD 810G



Sealing
P67 (WWAN)
IP54 (WiFi Only)



Display
5.45", HD+
(1440x720)



Extensions to Accessories
Rear Pogo, RFID Reader,
Wearable, Trigger



Get real pocket-power with true smartphone-style ergonomics

Forget the notion that industrial mobile computers are big and heavy. With its beautiful design and compact pocket size and slim(11.65 mm thick), HF550X offers the best grip to reduce work fatigue.

Enterprise-class data capture

The HF550 is equipped with a 1D/2D scanner (dual action side scan trigger) that can capture barcodes quickly in any environment, and provides uninterrupted and reliable connection of various accessories through the interface port.

Supports wide range of wireless connections

2X2 MU-MIMO enables faster and more reliable Wi-Fi connectivity than wired, Bluetooth 5.0 supports connectivity to peripherals at a wider, faster speed with lower power. LTE is also available, ensuring connectivity to the outside world.

Powerful durability and lifecycle

HF550X is IP67 for rain or dusty use and has a 1.2m drop specification. In addition, unlike consumer smartphones with very short lifecycles, HF550X offers up to eight years(4+4) of maintenance service support to save on maintenance costs compared to commercial smartphones.

Supports fingerprint function for enhanced job security and authentication

HF550X provides fingerprint registration to enhance job security and facilitate authentication.

Business Optimization solution BOS™ software support

Bluebird Business Optimizing Solutions(BOS™) is designed to help enterprise organizations from app development to terminal deployment for business performance and convenience.

Power every minute of every workday

With a 4000mAh battery available for 1.5 times the shift time, it reduces the business downtime caused by terminal charging.

SPECIFICATIONS

PERFORMANCE CHARACTERISTICS	
CPU	Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz
Operating System	Android 10 ; Upgradeable to Android 14
Memory	4 GB RAM / 32 GB UFS 4 GB RAM / 64 GB UFS (Optional)

PHYSICAL CHARACTERISTICS	
Dimensions (L x W x D)	154.4 x 74.8 x 11.65mm
Weight	205g
Display	5.45" HD+ (1440 x 720), TFT-IPS
Imager Window	Corning® Gorilla® Glass 3
Touchpanel	Capacitive multi-touch / Stylus, Glove, Wet
Backlight	LED backlight
Power	Replaceable Battery 3.8V / 4000mAh BOS™ PowerManager Station
Expansion Slot	MicroSD 32GB SDHC, up to 128GB SDXC
SIM / SAM	Hybrid Dual SIM Slot (2 Nano SIM or 1 Nano SIM / 1 Micro SD) - 2'nd Nano SIM is supported by micro SD Card Slot
Interface	USB Type C Connector (USB 2.0) Docking Connector (Charging) Rear 10-pin connector
Notification	Audible tone; multi-color LEDs; vibration
Keypad	On-screen keypad and Enterprise Keyboard power button; volume up/down buttons dual-action side scan triggers
Voice and Audio	Dual noise-cancelling microphones; High-quality speaker phone, 3.5mm headset jack
PTT Hot Key	Support – available Active Key

WIRELESS WAN DATA AND VOICE COMMUNICATIONS	
Radio Frequency Band	(Optional) EMEA, Korea, Thailand, India - LTE FDD: B1/B3/B5/B7/B8/B20 - LTE TDD: B38/B40/B41 - WCDMA: B1/B5/B8 - GSM/EDGE : B3/B8 Latin America, Australia, ANZ, Taiwan - LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 - LTE TDD: B40 - WCDMA: B1/B2/B5/B8 - GSM/EDGE : B2/B3/B5/B8 Japan - LTE FDD: B1/B3/B8/B18/B19/B26 - LTE TDD: B41 - WCDMA: B1/B6/B8/B19 North America - LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 - WCDMA: B2/B4/B5 China - LTE FDD: B1/B3/B5/B8 - LTE TDD: B38/ B39/ B40/ B41 - WCDMA: B1/ B8 - GSM/EDGE : B3/ B8
GPS	(for WWAN only) A-GPS, GLONASS, BEIDOU, Galileo

WIRELESS LAN	
Radio	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w/mc IPv4, IPv6, Wi-Fi™ certified 2x2 MU-MIMO
Data Rates	5GHz: 802.11a/n/ac — up to 866.7 Mbps 2.4GHz: 802.11b/g/n — up to 300 Mbps
Security and Encryption	WEP (40 or 104 bit) ; WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP, and AES) - EAPTTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PE APv0- MSCHAPv2, PE APv1-EAP-GTC, EAP Fast and LEA

WIRELESS PAN	
Bluetooth	Bluetooth 5.0 BLE , Class 2

COMMUNICATION AND MESSAGING	
VoIP / PTT	

DATA CAPTURE	
Scanning	1D/2D omnidirectional imager (dual-action side scan triggers)
Camera	Rear 13MP with flash, Auto focus
NFC	ISO 14443 Type A and B; F; FeliCa, and ISO 15693 cards, MiFare
RFID	(Optional- WLAN SKU Only) UHF RFID (Nominal Read Range : up to 40cm)

SENSOR	
Light Sensor	Ambient Light
Motion Sensor	Proximity, Gyro, Accelerometer, E-Compass

USER ENVIRONMENT	
Operating Temp	-10°C to 50°C / 14°F to 122°F
Storage Temp	-30°C to +70°C / -22°F to +158°F
Humidity	95% non-condensing
Drop Spec	1.2m / 4ft. drop per MIL-STD 810G
Tumble Spec	300 tumbles, 1.6 ft./0.5 m
Sealing	WiFi SKU : IP54 WWAN SKU : IP67
Vibration	4G peak, 5 Hz to 2 kHz, 1 hour duration per axis
Thermal Shock	-40° C to 70° C / -40° F to 158° F rapid transition 10 cycles (1 cycle = 1.25 hours at -40°C and 1.25 hours at 70°C)
Electrostatic Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge

ACCESSORIES	
In-box	Wall Adapter, USB Cable, SIM tooling pin
Additional	Wrist Strap, Protective Film, Protective Case (TBD), Multi-slot charging Cradle (TBD)

* Specification subject to change without notice